

or lengths. Suitable for insulation inside of closed conduits and cable ducting systems and on or under plaster, but only as part of signal or control circuits.

Under individual part numbers, different core insulation colours and package types are offered for diverse application types. More and more automatic harnessing machines are made use of by the manufacturing sector for the harnessing of such hook-up wires. Especially therefore, we offer parts with embossed cable marking instead of printing and which are delivered inside big one-way cardboard boxes with enhanced cable amount per box. Further standard package types are classic coils with standard order length as well as spools with wound, fix standard length of this wire.

Package types:

Color: Seven-digit part without final, alphabetic character

Plastic spool: Eight-digit part with final letter "S" on the eighth place

Small version of big one-way cardboard box: Eight-digit part with final letter "C" on the eighth place

Big version of big one-way cardboard box: Eight-digit part with final letter "E" on the eighth place

Design

Design	acc. to EN 50255-3-31
Certification	The cable is characterized with the «H05» HAA-sign or HAA-identification thread.
	Classification of fire behaviour according to EN 1363-1-6 and EN 50276 (article/dimension range see www.lappdata.com/typ)
Conductor	five wire strands of bare copper, acc. to IEC 60228 resp. EN 60228, class 5
Insulation	PVC compound type B1 acc. to EN 50363-3

Electrical properties at 20 °C

Nominal voltage	U ₀ /U: 300 / 500 V
Test voltage	3000 V AC

Mechanical and thermal properties

Minimum bending radius	at intended use 4 x outer diameter for cautious bending 2 x outer diameter
Temperature range	Fixed installation (without vibration): -40 °C to +70 °C laying/ handling: min. +5 °C short circuit and ground leakage max. +140 °C ambient temperature at storage: max. +40 °C max. conductor temperature: +70 °C
Flammability	acc. to IEC 60332-1-2 resp. EN 60332-1-2

Tests	acc. to IEC 60811 resp. EN 60811, EN 50345, EN 50346
-------	--

General requirements These cables conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see www.lappdata.com/typ) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Note Trade product, no Lapp product