



Color: ■ dark gray



Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	400 V
Rated current	41 A

Physical data

Width	12.3 mm / 0.484 inches
Height	10.74 mm / 0.423 inches
Depth	23.9 mm / 0.941 inches
Jumper assignment	1-2



Mechanical data		
Use		with locking function

Material data		
Note (material data)		Information on material specifications can be found here
Color		dark gray
Insulation material (main housing)		Polyamide (PA66)
Weight of insulation material		0.45 g
Weight		2.9 g

Environmental requirements		
Continuous operating temperature		-60 ... +105 °C

Commercial data		
PU (SPU)		5 pcs
Packaging type		Bag
Country of origin		CN
GTIN		4055144067873
Customs tariff number		85366990990

Product Classification		
UNSPSC		39121421
ETIM 9.0		EC000489
ETIM 10.0		EC000489
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search		
Environmental Product Compliance 221-941		

Documentation

Bid Text		
221-941	xml 2.95 KB	
221-941	docx 27.49 KB	

CAD/CAE-Data


CAD data

2D/3D Models 221-941




Installation Notes

Commoning



Extending the N and PE (ground) distribution via jumper

Commoning



Insert the jumper without a locking function into open clamping units.

Commoning




Without a locking function:
The jumper without a locking function is plugged into the splicing connectors.

Commoning



Remove the locking mechanism for intentional jumper removal.



Remove the jumper from open clamping units.