

Data Sheet | Item Number: 2202-1911

Regletă conexiuni siguranță 2 conductori; cu suport siguranță pivotant; cu poziție șunt suplimentar; pentru 5 siguranțe miniaturale de 20 mm; cu buton cu reținere; fără indicare siguranță fuzibilă lentă; pentru șină DIN 35 x 15 și 35 x 7,5; 2,5 mm²; CAGE CLAMP® înclichetare; 2,50 mm²; gri

<https://www.wago.com/2202-1911>



Electrical data

Ratings per	IEC/EN 60947-7-3		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	250 V	-	-
Rated surge voltage	6 kV	-	-
Rated current	6.3 A	-	-

Ratings per IEC/EN – Notes

Ratings (note) Electrical ratings are given by the fuse.

Approvals per	UL 1059		
Use group	B	C	D
Rated voltage	250 V	250 V	250 V
Rated current	10 A	10 A	-

Approvals per	CSA 22.2 No 158		
Use group	B	C	D
Rated voltage	250 V	250 V	250 V
Rated current	10 A	10 A	10 A

Ex information

Reference hazardous areas	See "Downloads – Documentation – Additional Information: Technical Section; Technical Explications"
Ratings per	ATEX: PTB 20 ATEX 1007 U / IECEx: PTB 20.0013U (Ex ec IIC Gc)
Rated voltage EN (Ex e II)	275 V
Rated current (Ex e II)	6.3 A

Power Loss

Power loss P _I max. overload and short-circuit protection (individual arrangement)	1.6 W
Power loss P _I max. overload and short-circuit protection (group arrangement)	1.6 W
Power loss P _I max. short-circuit protection (individual arrangement)	1.6 W
Power loss P _I max. short-circuit protection (group arrangement)	1.6 W

General

Fuse receptacle	pivoting
Fuse type	Cylindrical fuse; 5 x 20 mm

Connection data

Clamping units	2
Total number of potentials	1
Number of levels	1
Number of jumper slots	3

Connection 1

Connection technology	Push-in CAGE CLAMP®
Actuation type	Push-button
Connectable conductor materials	Copper
Nominal cross-section	2,5 mm ²
Solid conductor	0,25 ... 4 mm ² / 22 ... 12 AWG
Solid conductor; push-in termination	0,75 ... 4 mm ² / 18 ... 12 AWG
Fine-stranded conductor	0,25 ... 4 mm ² / 22 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	0,25 ... 2,5 mm ² / 22 ... 14 AWG
Fine-stranded conductor; with ferrule; push-in termination	1 ... 2,5 mm ² / 18 ... 14 AWG
Note (conductor cross-section)	Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.
Strip length	10 ... 12 mm / 0.39 ... 0.47 inci

Front-entry wiring

Width	6,2 mm / 0.244 inci
Height	72,9 mm / 2.87 inci
Depth from upper-edge of DIN-rail	57,6 mm / 2.268 inci

Mounting type	DIN-35 rail
Marking level	Center/side marking

Note (material data)	Information on material specifications can be found here
Color	gri
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.259 MJ
Actuator color	orange
Weight	14.3 g

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

ETIM 9.0	EC000899
ETIM 8.0	EC000899
PU (SPU)	50 Buc.
Packaging type	Box
Country of origin	DE
GTIN	4055143962001
Customs tariff number	85369095000

RoHS Compliance Status	Compliant,No Exemption
------------------------	------------------------