



### HW Fire protection outlet box BS134

Order number: 7500057

Type: BS134

The missing brick for perfect protection

- Unique, new technology for compliance with VDE for cable outlets in fire protection walls
- Also approved for through-wiring
- For 2 cables or one M25 electrical installation pipe
- Easy installation as usual
- Fast, simple and secure
- ETA approval up to EI90
- Approved for ceilings up to EI90

#### Dimensions

|                       |            |
|-----------------------|------------|
| Depth                 | 55 - 55 mm |
| Diameter              | 35 mm      |
| Internal depth        | 53 mm      |
| Milling hole diameter | Ø 35 mm    |

#### Material

|                 |    |
|-----------------|----|
| Lid material    | PS |
| Socket material | PP |

Properties

|                           |       |
|---------------------------|-------|
| Colour                    | Black |
| Degree of protection (IP) | IP30  |
| Installation type         | HW    |

Technical features

|                              |         |
|------------------------------|---------|
| Cable entry                  | 2       |
| Design voltage               | 400 V   |
| max. cross section           | 2,5 mm² |
| Pipe entry M25               | 1       |
| Suitable for sheet thickness | 5-30 mm |

Certificates & standards

|                |             |
|----------------|-------------|
| Approval       | ETA-21/0879 |
| CE             | true        |
| Glow wire test | 850 °C      |
| REACH          | false       |
| RoHS           | true        |

Accessories

|               |      |
|---------------|------|
| Equipped with | None |
|---------------|------|